

HCS-4340CAT/50 Multi-function Connector



Functions

- Direct or indirect connection with discussion unit, 3-key voting unit and channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented "MCA-STREAM" technology
- Automatic recovery facility, supporting "PnP"(plug and play)

Interconnections

- Built-in 4 x RJ45 interface:
 - ◆ HCS-4340CAT/50 can connect 1 3-key voting unit, 1 chairman unit and 1 channel selector
- Ø 3.5 mm socket for loudspeaker
- 2.1 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

Technical Specifications

Electrical

Max. consumption.....2.1 W

Mechanical

Mounting.....Fixed mounting
 Dimensions (h x w x d).....35 x 170 x 112 mm
 Weight.....0.9 kg
 Color.....Charcoal gray (PANTONE Cool Gray 11 C)

Ordering Information

HCS-4340CAT/50.....Multi-function Connector (for connection to 1 chairman unit + 1 3-key voting unit + 1 channel selector, charcoal gray)

HCS-4340CAF/50 Multi-function Connector



Functions

- Direct or indirect connection with discussion unit, 5-key voting unit and channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented "MCA-STREAM" technology
- Automatic recovery facility, supporting "PnP"(plug and play)

Interconnections

- Built-in 4 x RJ45 interface:
 - ◆ HCS-4340CAF/50 can connect 1 5-key voting unit, 1 chairman unit and 1 channel selector
- Ø 3.5 mm socket for loudspeaker
- 2.1 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

Technical Specifications

Electrical

Max. consumption.....2.1 W

Mechanical

Mounting.....Fixed mounting
 Dimensions (h x w x d).....35 x 170 x 112 mm
 Weight.....0.9 kg
 Color.....Charcoal gray (PANTONE Cool Gray 11 C)

Ordering Information

HCS-4340CAF/50.....Multi-function Connector (for connection to 1 chairman unit + 1 5-key voting unit + 1 channel selector, charcoal gray)

HCS-4340DAT/50 Multi-function Connector



Functions

- Direct or indirect connection with discussion unit, 3-key voting unit and channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented "MCA-STREAM" technology
- Automatic recovery facility, supporting "PnP"(plug and play)

Interconnections

- Built-in 4 x RJ45 interface:
 - ◆ HCS-4340DAT/50 can connect 1 3-key voting unit, 1 delegate unit and 1 channel selector
- Ø 3.5 mm socket for loudspeaker
- 2.1 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

Technical Specifications

Electrical

Max. consumption.....2.1 W

Mechanical

Mounting.....Fixed mounting
 Dimensions (h x w x d).....35 x 170 x 112 mm
 Weight.....0.9 kg
 Color.....Charcoal gray (PANTONE Cool Gray 11 C)

Ordering Information

HCS-4340DAT/50.....Multi-function Connector (for connection to 1 delegate unit + 1 3-key voting unit + 1 channel selector, charcoal gray)

HCS-4340DAF/50 Multi-function Connector



Functions

- Direct or indirect connection with discussion unit, 5-key voting unit and channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented "MCA-STREAM" technology
- Automatic recovery facility, supporting "PnP"(plug and play)

Interconnections

- Built-in 4 x RJ45 interface:
 - ◆ HCS-4340DAF/50 can connect 1 5-key voting unit, 1 delegate unit and 1 channel selector
- Ø 3.5 mm socket for loudspeaker
- 2.1 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

Technical Specifications

Electrical

Max. consumption.....2.1 W

Mechanical

Mounting.....Fixed mounting
 Dimensions (h x w x d).....35 x 170 x 112 mm
 Weight.....0.9 kg
 Color.....Charcoal gray (PANTONE Cool Gray 11 C)

Ordering Information

HCS-4340DAF/50.....Multi-function Connector (for connection to 1 delegate unit + 1 5-key voting unit + 1 channel selector, charcoal gray)

HCS-4340HDAT/50 Multi-function Connector



Functions

- Direct or indirect connection with discussion unit, 3-key voting unit and channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented "MCA-STREAM" technology
- Automatic recovery facility, supporting "PnP"(plug and play)

Interconnections

- Built-in 4 x RJ45 interface:
 - ◆ HCS-4340HDAT/50 can connect 1 3-key voting unit and 1 channel selector
- Ø 3.5 mm socket for loudspeaker
- 6P mini DIN socket for handheld microphone
- 2.1 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

Technical Specifications

Electrical

Max. consumption.....2.1 W

Mechanical

Mounting.....Fixed mounting
 Dimensions (h x w x d).....35 x 170 x 112 mm
 Weight.....0.9 kg
 Color.....Charcoal gray (PANTONE Cool Gray 11 C)

Ordering Information

HCS-4340HDAT/50.....Multi-function Connector (for connection to 1 handheld delegate unit + 1 3-key voting unit + 1 channel selector, charcoal gray)

HCS-4340HDAF/50 Multi-function Connector



Functions

- Direct or indirect connection with discussion unit, 5-key voting unit and channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented "MCA-STREAM" technology
- Automatic recovery facility, supporting "PnP"(plug and play)

Interconnections

- Built-in 4 x RJ45 interface:
 - ◆ HCS-4340HDAF/50 can connect 1 5-key voting unit and 1 channel selector
- Ø 3.5 mm socket for loudspeaker
- 6P mini DIN socket for handheld microphone
- 2.1 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

Technical Specifications

Electrical

Max. consumption.....2.1 W

Mechanical

Mounting.....Fixed mounting
 Dimensions (h x w x d).....35 x 170 x 112 mm
 Weight.....0.9 kg
 Color.....Charcoal gray (PANTONE Cool Gray 11 C)

Ordering Information

HCS-4340HDAF/50.....Multi-function Connector (for connection to 1 handheld delegate unit + 1 5-key voting unit + 1 channel selector, charcoal gray)

HCS-4340HDAT/50P Multi-function Connector



Functions

- Direct or indirect connection with discussion unit, 3-key voting unit and channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented "MCA-STREAM" technology
- Automatic recovery facility, supporting "PnP"(plug and play)
- +48 V phantom power available at microphone input, a condenser microphone can be connected directly

Interconnections

- Built-in RJ45 interfaces can connect 1 3-key voting unit and 1 channel selector
- Ø 3.5 mm socket for loudspeaker
- 6P mini DIN socket for condenser microphone, +48 V phantom power
- 2.1 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

Technical Specifications

Electrical

Max. consumption.....2.1 W

Mechanical

Mounting.....Fixed mounting
 Dimensions (h x w x d).....35 x 170 x 112 mm
 Weight.....0.9 kg
 Color.....Charcoal gray (PANTONE Cool Gray 11 C)

Ordering Information

HCS-4340HDAT/50P...Multi-function Connector (for connection to 1 condenser microphone + 1 3-key voting unit + 1 channel selector, +48 V phantom power, charcoal gray)

HCS-4340HDAF/50P Multi-function Connector



Functions

- Direct or indirect connection with discussion unit, 5-key voting unit and channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented "MCA-STREAM" technology
- Automatic recovery facility, supporting "PnP"(plug and play)
- +48 V phantom power available at microphone input, a condenser microphone can be connected directly

Interconnections

- Built-in RJ45 interfaces can connect 1 5-key voting unit and 1 channel selector
- Ø 3.5 mm socket for loudspeaker
- 6P mini DIN socket for condenser microphone, +48 V phantom power
- 2.1 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

Technical Specifications

Electrical

Max. consumption.....2.1 W

Mechanical

Mounting.....Fixed mounting
 Dimensions (h x w x d).....35 x 170 x 112 mm
 Weight.....0.9 kg
 Color.....Charcoal gray (PANTONE Cool Gray 11 C)

Ordering Information

HCS-4340HDAF/50P...Multi-function Connector (for connection to 1 condenser microphone + 1 5-key voting unit + 1 channel selector, +48 V phantom power, charcoal gray)

HCS-4340B/50 Multi-function Connector



Functions

- Direct or indirect connection with channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented “MCA-STREAM” technology
- Automatic recovery facility, supporting "PnP" (plug and play)

Interconnections

- Built-in 4 x RJ45 interface:
 - ◆ HCS-4340B/50 can connect 4 pcs channel selectors
- 2.1 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

Technical Specifications

Electrical

Max. consumption.....2.1 W

Mechanical

Mounting.....Fixed mounting
 Dimensions (h x w x d).....35 x 170 x 112 mm
 Weight.....0.9 kg
 Color.....Charcoal gray (PANTONE Cool Gray 11 C)

Ordering Information

HCS-4340B/50.....Multi-function Connector (for connection to 4 pcs of channel selectors, charcoal gray)

HCS-4340DT/50 Multi-function Connector



Functions

- Direct or indirect connection with discussion unit or channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented “MCA-STREAM” technology
- Automatic recovery facility, supporting "PnP"(plug and play)

Interconnections

- Built-in 4 x RJ45 interface:
 - ◆ HCS-4340DT/50 can connect 2 delegate units and 2 channel selectors
- 2.1 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

Technical Specifications

Electrical

Max. consumption.....2.1 W

Mechanical

Mounting.....Fixed mounting
 Dimensions (h x w x d).....35 x 170 x 112 mm
 Weight.....0.9 kg
 Color.....Charcoal gray (PANTONE Cool Gray 11 C)

Ordering Information

HCS-4340DT/50.....Multi-function Connector (for connection to 2 delegate units + 2 channel selectors, charcoal gray)

System Connection

