

## HCS-5300CE/80 Wireless Chairman Unit with Voting and Channel Selection



### Features

- **Table, stylish and ergonomic design**
- **Wireless unit, easy setup and removal**
- **Hi-Fi loudspeaker**
- **Priority button**
- **Pluggable microphone**
- **System controls up to 1000 contribution units**
- **5 voting keys**
- **Transmitting up to 8 CHs high quality digital audio signals**
- **Built-in channel selector consists of up/down channel select keys and 2-digit channel indicator display**
- **Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor**
- **Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed**
- **Adopts 1~8 MHz transmission frequency, excellent immunity to RF interference from HF-driven lighting and mobile phones**
- **Microphone sensitivity and EQ individually adjustable**
- **Built-in rechargeable Lithium battery pack**

The stylish and ergonomically designed chairman unit has all the necessary facilities to enable the user to chair a conference. Similar in appearance and function to HCS-5300DE/80 Delegate Unit, the HCS-5300CE/80 Chairman Unit includes an extra microphone priority button. When pressed, the priority button causes all currently active microphones to be switched off temporarily or permanently, allowing the chairman to take control of the meeting. Separate rechargeable Lithium battery packs can be removed and replaced in a matter of seconds, providing maximum flexibility in recharge scheduling.

### Functions

- Compliant with IEC 60914
- Based on TAIDEN originated dirATC-digital infrared Audio Transmitting and Control technologies
- Infrared transmitting carrier frequency conforms to IEC 61603-7, DQPSK digital modulation/demodulation technology
- System controls up to 1000 contribution units
- Transmitting up to 8 CHs high quality digital audio signals
- Every delegate unit is assigned an individual ID for convenient setup and to avoid double ID forever
- Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor
- Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed
- Adopts 1~8 MHz transmission frequency, excellent immunity to RF interference from HF-driven lighting and mobile phones
- Stem microphone can be unplugged during adjournment, easy to maintain
- Mini-microphone, with foam windshield
- Hi-Fi loudspeaker, minimal feedback
- Ø 3.5 mm stereo headphone jack for headphone with controllable volume
- Microphone On/Off button, 5 voting keys
- Built-in channel selector (operable only when earphone is inserted)
- Microphone sensitivity and EQ individually adjustable
- System implements the following facilities when operated in stand-alone mode:
  - ◆ "ACTIVE MICS", set the number of delegates permitted to speak at the same time (1/2/3/4)
  - ◆ "OPEN" mode, if Mic. active limit has been reached, next microphone cannot be turned on when pressing "Mic. On/Off" button
  - ◆ "OVERRIDE" mode, if Mic. active limit has been reached, when pressing "Mic. On/Off" button, next microphone is turned on and the first active microphone is turned off
  - ◆ "VOICE" mode, Mic. sensitivity and close time adjustable, built-in "Flash-on" technology for quick voice control
  - ◆ Simultaneous interpretation
- In combination with the corresponding software modules, multiform voting can be implemented:
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Questionnaire: 1/2/3/4/5
  - ◆ Audience response: --/-/0/+/++
- Key-press sign-in
- Automatic video tracking, when cooperating with camera and video switcher unit
- Activatable at any time provided that the total number of active microphones (including the active microphone of the chairman) is within the maximum of 4 active microphones allowed by the system
- Priority button to switch off or to mute the speaking units according to preset
- System supports up to 20 chairman units, while only 1 chairman unit has the control facilities listed above

- Built-in rechargeable Lithium battery operation duration: 14.4 hours when microphone is continuously on; 48 hours when microphone is off

**Controls and Indicators**

- Graphic 64x48 LCD with back-lighting for displaying channel number, language name, battery capacity and signal icon
- Built-in channel selector consists of up/down channel select keys and 2-digit channel indicator display
- Uni-directional electret condenser microphone with two-color illuminated ring
- Charging indicator
- Fully charged indicator
- Power switch
- Headphone volume control button
- Five voting keys with indicators
- Microphone On/Off button with indicator
- Priority button

**Interconnections**

- Socket for pluggable microphone
- Ø 3.5 mm stereo headphone jack
- Power adapter interface

**Technical Specifications**

**Electrical**

**Headphone connection**

Frequency response.....20 Hz to 20 kHz (-3dB)  
 Headphone load impedance.....≥16 Ohm × 2  
 Headphone output.....10 mW

**Microphone**

Transducer.....Electret-condenser  
 Polar pattern.....Uni-directional  
 Sensitivity.....-46 dBV/Pa  
 Frequency response.....30 Hz to 20 kHz  
 Directionality 0°/180°.....>20 dB (1 kHz)  
 Equivalent noise.....20 dBA (SPL)  
 Max.SPL.....125 dB (THD<3%)

**Interface data**

Connector.....Ø 3.5 mm stereo jack for headphone

**Operation time of battery pack**

When mic. is continuously on.....Approx. 14.4 hours  
 When mic. is off.....Approx. 48 hours

**Mechanical**

Mounting.....Tabletop  
 Dimensions (h x w x d) (w/o Mic.).....73 x 184 x 134 mm  
 Weight  
 Excl. battery.....0.5 kg  
 Incl. battery.....0.8 kg  
 Color.....Silver (PANTONE 428C) / Charcoal gray (PANTONE Cool Gray 11C)

**Ordering Information**

HCS-5300CE\_S/80.....Digital IR Wireless Chairman Unit (discussion, voting, 1+7 CHs, silver, excl. battery)  
 HCS-5300CE\_G/80.....Digital IR Wireless Chairman Unit (discussion, voting, 1+7 CHs, charcoal gray, excl. battery)

## HCS-5300DE/80 Wireless Discussion Unit with Voting and Channel Selection



### Features

- **Table, stylish and ergonomic design**
- **Wireless unit, easy setup and removal**
- **Hi-Fi loudspeaker**
- **Pluggable microphone**
- **System controls up to 1000 contribution units**
- **5 voting keys**
- **Transmitting up to 8 CHs high quality digital audio signals**
- **Built-in channel selector consists of up/down channel select keys and 2-digit channel indicator display**
- **Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor**
- **Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed**
- **Excellent immunity to RF interference from HF-driven lighting and mobile phones**
- **Microphone sensitivity and EQ individually adjustable**
- **Built-in rechargeable Lithium battery pack**

The multi-functional wireless delegate unit meets the demands of even the largest conferences and provides facilities for speaking, listening, voting and selecting language channels. It has excellent immunity to RF interference from mobile phones and features a channel selector and a headphone connection. Channel selection is automatically limited to the number of language channels available. The loudspeaker offers superior acoustics with minimal feedback, for enhanced intelligibility.

Separate rechargeable Lithium battery packs can be removed and replaced in a matter of seconds, providing maximum flexibility in recharge scheduling.

### Functions

- Compliant with IEC 60914
- Based on TAIDEN originated dirATC-digital infrared Audio Transmitting and Control technologies
- Infrared transmitting carrier frequency conforms to IEC 61603-7, DQPSK digital modulation/demodulation technology
- System controls up to 1000 contribution units
- Transmitting up to 8 CHs high quality digital audio signals
- Every delegate unit is assigned an individual ID for convenient setup and to avoid double ID forever
- Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor
- Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed
- Excellent immunity to RF interference from HF-driven light and mobile phones
- Stem microphone can be unplugged during adjournment, easy to maintain
- Mini-microphone, with foam windshield
- Hi-Fi loudspeaker, minimal feedback
- Ø 3.5 mm stereo headphone jack for headphone with controllable volume
- Microphone On/Off button, 5 voting keys
- Built-in channel selector (operable only when earphone is inserted)
- Microphone sensitivity and EQ individually adjustable
- System implements the following facilities when operated in stand-alone mode:
  - ◆ "ACTIVE MICS", set the number of delegates permitted to speak at the same time (1/2/3/4)
  - ◆ "OPEN" mode, if Mic. active limit has been reached, next microphone cannot be turned on when pressing "Mic. On/Off" button
  - ◆ "OVERRIDE" mode, if Mic. active limit has been reached, when pressing "Mic. On/Off" button, next microphone is turned on and the first active microphone is turned off
  - ◆ "VOICE" mode, Mic. sensitivity and close time adjustable, built-in "Flash-on" technology for quick voice control
  - ◆ Simultaneous interpretation
- In combination with the corresponding software modules, multiform voting can be implemented:
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Questionnaire: 1/2/3/4/5
  - ◆ Audience response: --/-/0/+/++
- Key-press sign-in
- Automatic video tracking, when cooperating with camera and video switcher unit
- Built-in rechargeable Lithium battery operation duration: 14.4 hours when microphone is continuously on; 48 hours when microphone is off

**Controls and Indicators**

- Graphic 64×48 LCD with back-lighting for displaying channel number, language name, battery capacity, and signal icon
- Built-in channel selector consists of up/down channel select keys and 2-digit channel indicator display
- Uni-directional electret condenser microphone with two-color illuminated ring
- Charging indicator
- Fully charged indicator
- Power switch
- Headphone volume control button
- Five voting keys with indicators
- Microphone On/Off button with indicator

**Interconnections**

- Socket for pluggable microphone
- Ø 3.5 mm stereo headphone jack
- Power adapter interface

**Technical Specifications**

**Electrical**

**Headphone connection**

Frequency response.....20 Hz to 20 kHz (-3 dB)  
 Headphone load impedance.....≥16 Ohm × 2  
 Headphone output.....10 mW

**Microphone**

Transducer.....Electret-condenser  
 Polar pattern.....Uni-directional  
 Sensitivity.....-46 dBV/Pa  
 Frequency response.....30 Hz to 20 kHz  
 Directionality 0°/180°.....>20 dB (1 kHz)  
 Equivalent noise.....20 dBA (SPL)  
 Max.SPL.....125 dB (THD<3%)

**Interface data**

Connector.....Ø 3.5 mm stereo jack for headphone

**Operation time of battery pack**

When mic. is continuously on.....Approx. 14.4 hours  
 When mic. is off.....Approx. 48 hours

**Mechanical**

Mounting.....Tabletop  
 Dimensions (h x w x d) (w/o Mic.).....73 x 184 x 134 mm  
 Weight  
 Excl. battery.....0.5 kg  
 Incl. battery.....0.8 kg  
 Color.....Silver (PANTONE 428C) / Charcoal gray (PANTONE Cool Gray 11C)

**Ordering Information**

HCS-5300DE\_S/80.....Digital IR Wireless Delegate Unit (discussion, voting, 1+7 CHs, silver, excl. battery)  
 HCS-5300DE\_G/80.....Digital IR Wireless Delegate Unit (discussion, voting, 1+7 CHs, charcoal gray, excl. battery)

## HCS-5301D/80 Wireless Discussion Unit with Dual Channel Selection



### Features

- Table, stylish and ergonomic design
- Wireless unit, easy setup and removal
- Hi-Fi loudspeaker
- Pluggable microphone
- System controls up to 1000 contribution units
- Transmitting up to 8 CHs high quality digital audio signals
- Built-in dual channel selectors consist of up/down channel select keys and 2-digit channel indicator display
- The microphone on/off buttons provide dual delegate identification, used for individual delegate identification on the left and right respectively and easy for automatic video tracking
- Can be used as a dual delegate unit
- Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor
- Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed
- Excellent immunity to RF interference from HF-driven lighting and mobile phones
- Microphone sensitivity and EQ individually adjustable
- Built-in rechargeable Lithium battery pack

The multi-functional wireless delegate unit can be used by two delegates. It provides facilities for speaking, listening and selecting language channels and has excellent immunity to RF interference from mobile phones. It features two separate headphone connections with individual volume control, two separate microphone on/off buttons and two separate channel selectors on both sides of the unit, allowing one unit to serve two delegates. The loudspeaker offers superior acoustics with minimal feedback, for enhanced intelligibility.

Separate rechargeable Lithium battery packs can be removed and replaced in a matter of seconds, providing maximum flexibility in recharge scheduling.

### Functions

- Compliant with IEC 60914
- Based on TAIDEN originated dirATC-digital infrared Audio Transmitting and Control technologies
- Infrared transmitting carrier frequency conforms to IEC 61603-7, DQPSK digital modulation/demodulation technology
- System controls up to 1000 contribution units
- Transmitting up to 8 CHs high quality digital audio signals
- Every delegate unit is assigned an individual ID for convenient setup and to avoid double ID forever
- Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor
- Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed
- Excellent immunity to RF interference from HF-driven light and mobile phones
- Stem microphone can be unplugged during adjournment, easy to maintain
- Mini-microphone, with foam windshield
- Hi-Fi loudspeaker, minimal feedback
- Two Ø 3.5 mm stereo headphone jacks for headphones with separate volume control
- With two separate microphone on/off buttons for individual microphone control and individual delegate identification
- Can be used as a dual delegate unit
- Built-in dual channel selectors (operable only when earphone is inserted)
- Microphone sensitivity and EQ individually adjustable
- System implements the following facilities when operated in stand-alone mode:
  - ◆ "ACTIVE MICS", set the number of delegates permitted to speak at the same time (1/2/3/4)
  - ◆ "OPEN" mode, if Mic. active limit has been reached, next microphone cannot be turned on when pressing "Mic. On/Off" button
  - ◆ "OVERRIDE" mode, if Mic. active limit has been reached, when pressing "Mic. On/Off" button, next microphone is turned on and the first active microphone is turned off
  - ◆ "VOICE" mode, Mic. sensitivity and close time adjustable, built-in "Flash-on" technology for quick voice control
  - ◆ Simultaneous interpretation
- Automatic video tracking, when cooperating with camera and video switcher unit

- Built-in rechargeable Lithium battery operation duration: 14.4 hours when microphone is continuously on; 48 hours when microphone is off

**Controls and Indicators**

- Two graphic 64×48 LCDs with back-lighting for channel number, language name, battery capacity and signal icon
- Built-in two channel selectors consist of up/down channel select keys and 2-digit channel indicator display
- Uni-directional electret condenser microphone with two-color illuminated ring
- Charging indicator
- Fully charged indicator
- Power switch
- Two headphone volume control buttons
- Two microphone On/Off buttons with indicator

**Interconnections**

- Socket for pluggable microphone
- 2 × Ø 3.5 mm stereo headphone jack
- Power adapter interface

**Technical Specifications**

**Electrical**

**Headphone connection**

Frequency response.....20 Hz to 20 kHz (-3dB)  
 Headphone load impedance.....≥16 Ohm × 2  
 Headphone output.....10 mW

**Microphone**

Transducer.....Electret-condenser  
 Polar pattern.....Uni-directional  
 Sensitivity.....-46 dBV/Pa  
 Frequency response.....30 Hz to 20 kHz  
 Directionality 0°/180°.....>20 dB (1 kHz)  
 Equivalent noise.....20 dBA (SPL)  
 Max.SPL.....125 dB (THD<3%)

**Interface data**

Connector.....2 x Ø 3.5 mm stereo jack for headphone

**Operation time of battery pack**

When mic. is continuously on.....Approx. 14.4 hours  
 When mic. is off.....Approx. 48 hours

**Mechanical**

Mounting.....Tabletop  
 Dimensions (h x w x d) (w/o Mic.).....73 x 184 x 134 mm  
 Weight  
 Excl. battery.....0.5 kg  
 Incl. battery.....0.8 kg  
 Color.....Silver (PANTONE 428C) / Charcoal gray (PANTONE Cool Gray 11C)

**Ordering Information**

HCS-5301D\_S/80.....Digital IR Wireless Delegate Unit (discussion, 1+7 CHs, 2 channel selectors, dual predefined position, silver, excl. battery)  
 HCS-5301D\_G/80.....Digital IR Wireless Delegate Unit (discussion, 1+7 CHs, 2 channel selectors, dual predefined position, charcoal gray, excl. battery)

## HCS-5302C/80 Wireless Chairman Unit



### Features

- **Table, stylish and ergonomic design**
- **Wireless unit, easy setup and removal**
- **Hi-Fi loudspeaker**
- **Priority button**
- **Pluggable microphone**
- **System controls up to 1000 contribution units**
- **Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor**
- **Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed**
- **Excellent immunity to RF interference from HF-driven lighting and mobile phones**
- **Microphone sensitivity and EQ individually adjustable**
- **Built-in rechargeable Lithium battery pack**

The stylish and ergonomically designed chairman unit has all the necessary facilities to enable the user to chair a conference. Similar in appearance and function to HCS-5302D Delegate Unit, the HCS-5302C Chairman Unit includes an extra microphone priority button. When pressed, the priority button causes all currently active microphones to be switched off temporarily or permanently, allowing the chairman to take control of the meeting. Separate rechargeable Lithium battery packs can be removed and replaced in a matter of seconds, providing maximum flexibility in recharge scheduling.

### Functions

- Compliant with IEC 60914
- Based on TAIDEN originated dirATC-digital infrared Audio Transmitting and Control technologies
- Infrared transmitting carrier frequency conforms to IEC 61603-7, DQPSK digital modulation/demodulation technology
- System controls up to 1000 contribution units
- Every delegate unit is assigned an individual ID for convenient setup and to avoid double ID forever
- Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor
- Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed
- Excellent immunity to RF interference from HF-driven light and mobile phones
- Stem microphone can be unplugged during adjournment, easy to maintain
- Mini-microphone, with foam windshield
- Hi-Fi loudspeaker, minimal feedback
- Ø 3.5 mm stereo headphone jack for headphone with controllable volume
- Microphone On/Off button
- Microphone sensitivity and EQ individually adjustable
- System implements the following facilities when operated in stand-alone mode:
  - ◆ "ACTIVE MICS", set the number of delegates permitted to speak at the same time (1/2/3/4)
  - ◆ "OPEN" mode, if Mic. active limit has been reached, next microphone cannot be turned on when pressing "Mic. On/Off" button
  - ◆ "OVERRIDE" mode, if Mic. active limit has been reached, when pressing "Mic. On/Off" button, next microphone is turned on and the first active microphone is turned off
  - ◆ "VOICE" mode, Mic. sensitivity and close time adjustable, built-in "Flash-on" technology for quick voice control
- Automatic video tracking, when cooperating with camera and video switcher unit
- Activatable at any time provided that the total number of active microphones (including the active microphone of the chairman) is within the maximum of 4 active microphones allowed by the system
- Priority button to switch off or to mute the speaking units according to preset
- System supports up to 20 chairman units, while only 1 chairman unit has the control facilities listed above
- Built-in rechargeable Lithium battery operation duration: 14.4 hours when microphone is continuously on; 48 hours when microphone is off

**Controls and Indicators**

- Graphic 64×48 LCD with back-lighting for displaying battery capacity and signal icon
- Uni-directional electret condenser microphone with two-color illuminated ring
- Charging indicator
- Fully charged indicator
- Power switch
- Headphone volume control button
- Microphone On/Off button with indicator
- Priority button

**Interconnections**

- Socket for pluggable microphone
- Ø 3.5 mm stereo headphone jack
- Power adapter interface

**Ordering Information**

- HCS-5302C\_S/80 .....Digital IR Wireless Chairman Unit  
(discussion, silver, excl. battery)
- HCS-5302C\_G/80 .....Digital IR Wireless Chairman Unit  
(discussion, charcoal gray, excl. battery)

**Technical Specifications**

**Electrical**

**Headphone connection**

Frequency response.....20 Hz to 20 kHz (-3dB)  
 Headphone load impedance.....≥16 Ohm × 2  
 Headphone output.....10 mW

**Microphone**

Transducer.....Electret-condenser  
 Polar pattern.....Uni-directional  
 Sensitivity.....-46 dBV/Pa  
 Frequency response.....30 Hz to 20 kHz  
 Directionality 0°/180°.....>20 dB (1 kHz)  
 Equivalent noise.....20 dBA (SPL)  
 Max.SPL.....125 dB (THD<3%)

**Interface data**

Connector.....Ø 3.5 mm stereo jack for headphone

**Operation time of battery pack**

When mic. is continuously on.....Approx. 14.4 hours  
 When mic. is off.....Approx. 48 hours

**Mechanical**

Mounting.....Tabletop  
 Dimensions (h x w x d) (w/o Mic.).....73 x 184 x 134 mm  
 Weight  
 Excl. battery.....0.5 kg  
 Incl. battery.....0.8 kg  
 Color .....Silver (PANTONE 428C) / Charcoal gray (PANTONE Cool Gray 11C)



## HCS-5302D/80 Wireless Discussion Unit



### Features

- Table, stylish and ergonomic design
- Wireless unit, easy setup and removal
- Hi-Fi loudspeaker
- Pluggable microphone
- System controls up to 1000 contribution units
- Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor
- Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed
- Excellent immunity to RF interference from HF-driven lighting and mobile phones
- Microphone sensitivity and EQ individually adjustable
- Built-in rechargeable Lithium battery pack

This wireless delegate unit meets the basic demands of most conferences. It provides facilities for speaking and listening and has excellent immunity to RF interference from mobile phones. The loudspeaker offers superior acoustics with minimal feedback, for enhanced intelligibility.

Separate rechargeable Lithium battery packs can be removed and replaced in a matter of seconds, providing maximum flexibility in recharge scheduling.

### Functions

- Compliant with IEC 60914
- Based on TAIDEN originated dirATC-digital infrared Audio Transmitting and Control technologies
- Infrared transmitting carrier frequency conforms to IEC 61603-7, DQPSK digital modulation/demodulation technology
- System controls up to 1000 contribution units
- Every delegate unit is assigned an individual ID for convenient setup and to avoid double ID forever
- Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor
- Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed
- Excellent immunity to RF interference from HF-driven light and mobile phones
- Stem microphone can be unplugged during adjournment, easy to maintain
- Mini-microphone, with foam windshield
- Hi-Fi loudspeaker, minimal feedback
- Ø 3.5 mm stereo headphone jack for headphone with controllable volume
- Microphone On/Off button
- Microphone sensitivity and EQ individually adjustable
- System implements the following facilities when operated in stand-alone mode:
  - ◆ "ACTIVE MICS", set the number of delegates permitted to speak at the same time (1/2/3/4)
  - ◆ "OPEN" mode, if Mic. active limit has been reached, next microphone cannot be turned on when pressing "Mic. On/Off" button
  - ◆ "OVERRIDE" mode, if Mic. active limit has been reached, when pressing "Mic. On/Off" button, next microphone is turned on and the first active microphone is turned off
  - ◆ "VOICE" mode, Mic. sensitivity and close time adjustable, built-in "Flash-on" technology for quick voice control
- Automatic video tracking, when cooperating with camera and video switcher unit
- Built-in rechargeable Lithium battery operation duration: 14.4 hours when microphone is continuously on; 48 hours when microphone is off

### Controls and Indicators

- Graphic 64×48 LCD with back-lighting for displaying battery capacity, signal icon and emission angle icon
- Uni-directional electret condenser microphone with two-color illuminated ring
- Charging indicator
- Fully charged indicator
- Power switch
- Headphone volume control button
- Microphone On/Off button with indicator

**Interconnections**

- Socket for pluggable microphone
- Ø 3.5 mm stereo headphone jack
- Power adapter interface

**Technical Specifications**

**Electrical**

**Headphone connection**

Frequency response.....20 Hz to 20 kHz (-3dB)  
 Headphone load impedance.....≥16 Ohm × 2  
 Headphone output.....10 mW

**Microphone**

Transducer.....Electret-condenser  
 Polar pattern.....Uni-directional  
 Sensitivity.....-46 dBV/Pa  
 Frequency response.....30 Hz to 20 kHz  
 Directionality 0°/180°.....>20 dB (1 kHz)  
 Equivalent noise.....20 dBA (SPL)  
 Max.SPL.....125 dB (THD<3%)

**Interface data**

Connector.....Ø 3.5 mm stereo jack for headphone

**Operation time of battery pack**

When mic. is continuously on.....Approx. 14.4 hours  
 When mic. is off.....Approx. 48 hours

**Mechanical**

Mounting.....Tabletop  
 Dimensions (h x w x d) (w/o Mic.).....73 x 184 x 134 mm  
 Weight  
 Excl. battery.....0.5 kg  
 Incl. battery.....0.8 kg  
 Color.....Silver (PANTONE 428C) / Charcoal gray (PANTONE Cool Gray 11C)

**Ordering Information**

HCS-5302D\_S/80.....Digital IR Wireless Delegate Unit (discussion, silver, excl. battery)  
 HCS-5302D\_G/80.....Digital IR Wireless Delegate Unit (discussion, charcoal gray, excl. battery)

**Conference Units Function list**

Type No.	Status	Discussion	Sign-in	Voting	Simultaneous interpretation
HCS-5300CE/80	chairman	√	√	√	1+7 CHs
HCS-5300DE/80	delegate	√	√	√	1+7 CHs
HCS-5301D/80	delegate	√			(1+7 CHs)×2
HCS-5302C/80	chairman	√			
HCS-5302D/80	delegate	√			